

# Rustikputz K 15



## Technical data

|                 |  |
|-----------------|--|
| Specific use(s) | Coating material                       |
| Density         | 1,80 g/cm <sup>3</sup>                 |
| Consumption     | 2,5 kg/m <sup>2</sup>                  |
| Gloss level     | Matt (in accordance with DIN EN 13300) |

## Components

|  |                                  |
|--|----------------------------------|
| Product Code/GISCODE                                       | M-DF01                           |
| Declaration of ingredients                                 | Synthetic resin plaster, aqueous |
| preservatives  | not contained                    |
| VOC content in accordance with Directive 2004/42/EC        | < 0.1 %                          |
| VOC content LEED [less water]                              | < 1 g/l                          |
| Solvent and plasticiser-free in accordance with VdL- RL 01 | < 1 g/l                          |
| Water-dilutable in accordance with 2004/42/EC (Decopaint)  | yes                              |
| Lead, cadmium, chromium VI *                               | yes                              |
| (* not contained in the formulation)                       | not contained                    |

## Environmental labels

## Building certifications

Suitability for DGNB criteria ENV 1.2 (2012) "Risks for the Local Environment"

| No. | Application site   | Product type  | QS 1 | QS 2 | QS 3 | QS 4 |
|-----|--|---|------|------|------|------|
| 2   | Liquid coatings on primarily mineral undercoats, such as concrete, masonry, mortar, filler, plaster, wallpaper, fleece or plasterboard. Floor space and thoroughfares such as underground car parks, access roads, etc are not taken into account. | Decorative paints, decorative fillers, dust-binding coatings, floor coverings without special resistance requirements, concrete protection coatings | yes  | yes  | yes  | yes  |

|   |   |              |
|---|---|--------------|
| Suitability for use in accordance with LEED | Category (IEQ4.2 - 2009)                                | flat topcoat |
|   | VOC limit   | 50 g/l       |
|   | Limit fulfilled   | yes          |
| Recycling share                             | not contained   |              |
| Production site                             | DAW SE<br>Roßdörfer Straße 50<br>DE-64372 Ober-Ramstadt |              |